

Application: gvSIG desktop - gvSIG bugs #3069

Corregir el gvSIG.sh para que ejecute correctamente en Windows con Busybox

12/16/2014 01:53 PM - Joaquín del Cerro Murciano

Status: Closed	% Done: 0%
Priority: Normal	Spent time: 0.00 hour
Assignee: Joaquín del Cerro Murciano	
Category:	
Target version: 2.1.0-2260	
Severity: Minor	Add-on version:
gvSIG version: 2.1.0	Add-on build:
gvSIG build:	Add-on resolve version:
Operative System:	Add-on resolve build:
Keywords:	Proyecto:
Has patch:	Hito:
Add-on name: Unknown	
Description	

Associated revisions

Revision 41888 - 12/16/2014 01:54 PM - Joaquín del Cerro Murciano

refs #3069, correcciones en el gvSIG.sh para que ejecute correctamente en windows con busybox.

Revision 41906 - 12/29/2014 12:37 AM - Joaquín del Cerro Murciano

refs #3069, actualizado el gvSIG.sh para que referencia al jre 7 en lugar de al 6.

History

#1 - 12/16/2014 01:55 PM - Joaquín del Cerro Murciano

- Status changed from New to Fixed

#2 - 12/18/2014 09:55 AM - Antonio Falciano

Hi Joaquín,

I've noticed the following line in the fix of this ticket:

```
PJH5="$GVSIG_INSTALL_FOLDER/gvSIG/extensiones/jre_6_windows_i586/jre"
```

...while we are using jre_7_windows_i586 now.

#3 - 12/27/2014 06:27 PM - Antonio Falciano

In order to launch gvSIG in Windows, we should have:

```
-Djava.library.path="%GVSIG_NATIVE_LIBS%\\"
```

instead of

```
-Djava.library.path="\${GVSIG_NATIVE_LIBS}"/usr/lib \
```

Furthermore, we should have all the needed DLLs in the *GVSIG_INSTALL_FOLDER/native* folder, because:

```
export GVSIG_NATIVE_LIBS="\${GVSIG_INSTALL_FOLDER}/native"
```

#4 - 01/26/2015 09:42 AM - Álvaro Anguix

- *Status changed from Fixed to Closed*